

TC1022型
TC1022-L型

改定前						
D	ピッチ	L2			Q1	H2
		標準	L+60	L+100	標準	標準
M7	1.00	92	163	203	27	38
M8	1.25	97	168	208	32	38
M9	1.25	99	170	210	34	38
M10	1.50	102	173	213	37	38
M11	1.50	106	177	217	41	39
M12	1.75	108	179	219	43	39
M14	2.00	112	182	222	47	41
M15	1.50	114	184	224	49	41
M16	2.00	117	187	227	52	43
M18	2.50	121	181	221	56	44
M20	2.50	125	185	225	60	45
M22	2.50	134	194	234	69	46
M24	3.00	140	200	240	72	48
M25	2.00	115	175	215	47	48
M26	1.50	115	175	215	47	48
M27	3.00	150	210	250	82	48
U 3/8	16	102	173	213	37	38
U 7/16	14	106	177	217	41	39
U 1/2	13	110	181	221	45	40
U 9/16	12	114	184	224	49	41
U 5/8	11	118	188	228	53	42
U 3/4	10	126	186	226	61	44
U 7/8	9	134	194	234	69	46
U 1	8	145	205	245	77	48
P 1/8	28	85	145	185	26	29
P 1/4	19	89	149	189	30	32
P 3/8	19	90	150	190	31	34
P 1/2	14	100	160	200	39	41
P 5/8	14	101	161	201	42	40
P 3/4	14	105	165	205	41	44



TC1022型
TC1022-L型

単位:mm

改定後(赤字のみ)								
D	ピッチ	L2			Q1		H2	
		標準	L+60	L+100	標準	L+60,100	標準	L+60,100
M7	1.00	92	163	203	27	38	38	27
M8	1.25	97	168	208	32	38	38	27
M9	1.25	99	170	210	34	38	38	27
M10	1.50	102	173	213	37	38	38	27
M11	1.50	106	177	217	41	39	39	28
M12	1.75	108	179	219	43	39	39	28
M14	2.00	112	182	222	47	41	41	31
M15	1.50	114	184	224	49	41	41	31
M16	2.00	117	187	227	52	43	43	33
M18	2.50	121	181	221	56	44	44	44
M20	2.50	125	185	225	60	45	45	45
M22	2.50	134	194	234	69	46	46	46
M24	3.00	140	200	240	72	48	48	48
M25	2.00	115	175	215	47	48	48	48
M26	1.50	115	175	215	47	48	48	48
M27	3.00	150	210	250	82	48	48	48
U 3/8	16	102	173	213	37	38	38	27
U 7/16	14	106	177	217	41	39	39	28
U 1/2	13	110	181	221	45	40	40	29
U 9/16	12	114	184	224	49	41	41	31
U 5/8	11	118	188	228	53	42	42	32
U 3/4	10	126	186	226	61	44	44	44
U 7/8	9	134	194	234	69	46	46	46
U 1	8	145	205	245	77	48	48	48
P 1/8	28	85	145	185	26	29	29	29
P 1/4	19	89	149	189	30	32	32	32
P 3/8	19	90	150	190	31	34	34	34
P 1/2	14	100	160	200	38	41	41	42
P 5/8	14	101	161	201	39	40	40	43
P 3/4	14	105	165	205	40	44	44	45